



BENCH SCALES


Laboratory | Industry | Food Industry





KERN Pictograms


 **Internal adjusting**
Quick setting up of the balance's accuracy with internal adjusting weight (motordriven)


 **Adjusting program CAL**
For quick setting up of the balance's accuracy. External adjusting weight required


 **EasyTouch**
Suitable for the connection, data transmission and control through PC or tablet


 **Memory**
Balance memory capacity, e.g. for article data, weighing data, tare weights, PLU etc.


 **Alibi memory**
Secure, electronic archiving of weighing results, complying with the 2014/31/EU standard.


 **KERN Universal Port (KUP)**
allows the connection of external KUP interface adapters, e.g. RS-232, RS-485, SB, Bluetooth, WIFI, Analogue, Ethernet etc. for the exchange of data and control commands, without installation effort


 **RS-232 Data interface**
To connect the balance to a printer, PC or network


 **RS-485 Data interface**
To connect the balance to a printer, PC or other peripherals. Suitable for data transfer over large distances. Network in bus topology is possible


 **USB Data interface**
To connect the balance to a printer, PC or other peripherals


 **Bluetooth® Data interface**
To transfer data from the balance to a printer, PC or other peripherals

 **WIFI Data interface**
To transfer data from the balance to a printer, PC or other peripherals


 **Control outputs**
(optocoupler, digital I/O)
To connect relays, signal lamps, valves, etc.


 **Analogue interface**
to connect a suitable peripheral device for analogue processing of the measurements


 **Interface for second balance**
For direct connection of a second balance


 **Network interface**
For connecting the scale to an Ethernet network


 **KERN Communication Protocol (KCP)**
It is a standardized interface command set for KERN balances and other instruments, which allows retrieving and controlling all relevant parameters and functions of the device. KERN devices featuring KCP are thus easily integrated with computers, industrial controllers and other digital systems


 **GLP/ISO log intern**
The balance displays weight, date and time, independent of a printer connection


 **GLP/ISO log Printer**
With weight, date and time. Only with KERN printers.


 **Piece counting**
Reference quantities selectable. Display can be switched from piece to weight


 **Recipe level A**
The weights of the recipe ingredients can be added together and the total weight of the recipe can be printed out


 **Recipe level B**
Internal memory for complete recipes with name and target value of the recipe ingredients. User guidance through display


 **Totalising level A**
The weights of similar items can be added together and the total can be printed out


 **Percentage determination**
Determining the deviation in % from the target value (100 %)


 **Weighing units**
Can be switched to e.g. nonmetric units. See balance model. Please refer to KERN's website for more details

 **Weighing with tolerance range (Checkweighing)**
Upper and lower limiting can be programmed individually, e.g. for sorting and dosing. The process is supported by an audible or visual signal, see the relevant model


 **Hold function**
(Animal weighing program)
When the weighing conditions are unstable, a stable weight is calculated as an average value


 **Protection against dust and water splashes IPxx**
The type of protection is shown in the pictogram


 **Suspended weighing**
Load support with hook on the underside of the balance


 **Battery operation**
Ready for battery operation. The battery type is specified for each device


 **Rechargeable battery pack**
Rechargeable set


 **Universal plug-in power supply**
with universal input and optional input socket adapters for
A) EU, CH, GB
B) EU, CH, GB, US
C) EU, CH, GB, US, AUS


 **Plug-in power supply**
230V/50Hz in standard version for EU, CH. On request GB, USA or AUS version available


 **Integrated power supply unit**
Integrated in balance. 230V/50Hz standard EU. More standards e.g. GB, USA or AUS on request


 **Weighing principle Strain gauges**
Electrical resistor on an elastic deforming body


 **Weighing principle Tuning fork**
A resonating body is electromagnetically excited, causing it to oscillate


 **Weighing principle Electromagnetic force compensation**
Coil inside a permanent magnet. For the most accurate weighings


 **Weighing principle Single cell technology**
Advanced version of the force compensation principle with the highest level of precision

 **Conformity Assessment**
The time required for conformity assessment is specified in the pictogram

 **DAkkS calibration possible (DKD)**
The time required for DAkkS calibration is shown in days in the pictogram

 **Factory calibration (ISO)**
The time required for Factory calibration is shown in days in the pictogram

 **Package shipment**
The time required for internal shipping preparations is shown in days in the pictogram

 **Pallet shipment**
The time required for internal shipping preparations is shown in days in the pictogram

KERN Models A-Z

572	31
A	
ABP	50-51
ABP-A	52
ABT-NM	48
ACS / ACJ	46-47
ADB / ADJ	43
ADS / ADT <small>NEW</small>	49
ALS-A / ALJ-A	44-45
B	
BFC	120-121
BIC	117
BID	118-119
BXC <small>NEW</small>	122
C	
CB Q1 / CB Q2 / CB P1	156
CCA	90-91
CCS	92-93
CDS	89
CE Hx	134
CFS	86
CH	165
CIB	83
CJ P / CJ X	159
CKE	87
CO Y1 / CO Y2 / CO Y5	158
CP P4 / CP Y4 / CP P1 / CP Y1 / CP P3	153
CP P2 / CP P7 / CP P8	154
CR Q1 / CR P1 / CR Y1	155
CT Q1 / CT P1 / CT P2	157
CPB	85
CXB/CXB-NM	84
D	
DAB	54
DBS	55
DE	102-103
DLB	56
DS	111
E	
ECB-N / ECE-N	59
EFS	11
EHA	15
EMB	12
EMB-V	13
EMS	14
EOB	100
EOC	104-105
EOE	99
EOS	101
EW-N / EG-N	34
EWJ	30

F	
FCB	61
FCE-N	60
FCF	67
FES / FEJ	40
FFN	72
FGE	66
FKB	62
FOB-LM	68
FOB-S / FOB-NS	69
FOB / FOB-NL	70
FXN / FXN-M	73
H	
HCB	167
HCD	169
HCN	168
HDB-N / HDB-XL	166
HFA	170
HFC	171
HFD	172-173
HFM	174
I	
IFB	110
IFC	108-109
IFS	88
IOC	106-107
IXC	112-113
K	
KBP-V20 IP65	148
KDP	135
KFA-V20	150
KFB-TM	145
KFC-TM	146
KFD-V20	149
KFD-V40 IP68	151
KFN-TM	145
KFP-V20 IP65	148
KFP-V20 IP67	149
KFP-V30	150
KFP-V40 IP68	151
KFS-TM	144
KFU-V20	150
KFU-V30	150
KGP	132
KIB-TM	145
KIP-V20M	149
KXC-TM	147
KXP-V20 IP65	148

N	
NFC <small>NEW</small>	129
NIB	128
NXC <small>NEW</small>	130
P	
PBJ / PBS	37
PCB	26-27
PCD	24
PCJ	28-29
PDS / PDT	38-39
PEJ / PES	36
PFB	25
PLJ / PLS	32
PNS / PNJ	33
PWS	35
R	
RIB	78
RPB	79
S	
SCD-4.0	179
SCD-4.0-PRO	180
SFB / SFB-H	76
SFE	114
SXC	74-75
T	
TGC	9
TGD	9
U	
UFA	123
UFC <small>NEW</small>	126
UIB	124
UID	125
UXC <small>NEW</small>	127
V	
VHB	161
W	
WTB	71
Y	
YKV	133
YRO-01 / -02 / -03	185



KERN Quick-Finder

How I quickly find the product I am looking for

Ahead of each product group allows you to base the search for a certain target group on weighing data you need such as readout, weighing capacity and main features for each model.

And it's as simple as that – find the product you want in 2 steps:

1. Go to the product group index on page 3
2. Pick the appropriate product group and find the product you want using the Quick-Finder



Plain, mobile, uncomplicated

Features

- Thanks to battery operation/rechargeable battery operation (optional), compact, light-weight construction, it is suitable for the use in several locations (production, warehouse, dispatch department, etc.)
- Particularly large weighing plate
- Very fast display: steady weight values within 2 s
- Simple and convenient 2-key operation

Technical data

- 1 KERN ECE**
- Large LCD display, digit height 21 mm
 - Dimensions weighing surface, plastic, W×D 320×260 mm
 - Net weight approx. 1,6 kg
- KERN ECB**, see larger picture
- Large backlit LCD display, digit height 21 mm
 - Dimensions weighing surface, stainless steel, W×D 320×260 mm
 - Net weight approx. 2,6 kg
- KERN ECE/ECB**
- Overall dimensions W×D×H 320×300×60 mm
 - Battery operation, 6×1.5 V AA standard, operating time up to 100 h, AUTO-OFF function to preserve the battery
 - Permissible ambient temperature 5 °C/35 °C

Accessories

- Internal rechargeable battery pack, operating time up to 30 h without backlight, charging time approx. 10 h, KERN PCB-A01, **€ 90,-**
- Rechargeable battery pack external, operating time up to 30 h without backlight, charging time approx. 10 h, KERN KS-A01, **€ 180,-**
- Tare pan made from stainless steel, ideal for weighing loose small parts as well as fruits, vegetables, etc., overall dimensions W×D×H 400×300×45 mm, KERN RFS-A02, **€ 75,-**
- External universal mains adapter, with universal input and optional input socket adapters for EU, CH, GB, US, KERN YKA-03N, **€ 38,-**
- Further details, plenty of further accessories and suitable printers see *Accessories*

STANDARD

CAL EXT

BATT

DMS

1 DAY

OPTION

ACCU

MULTI

DAKkS +3 DAYS

Model	Weighing capacity	Readability	Reproducibility	Linearity	Price excl. of VAT ex works €	Options	
	[Max] kg	[d] g	g	g		DAkkS Calibr. Certificate	
						DAkkS KERN	€
KERN							
ECE 10K-3N	10	5	5	± 20	120,-	963-128	124,-
ECE 20K-2N	20	10	10	± 40	120,-	963-128	124,-
ECE 50K-2N	50	20	20	± 80	120,-	963-128	124,-
ECB 10K-3N	10	5	5	± 20	140,-	963-128	124,-
ECB 20K-2N	20	10	10	± 40	140,-	963-128	124,-
ECB 50K-2N	50	20	20	± 80	140,-	963-128	124,-



Entry-level bench scale – mobile, practical, lightweight

Features

- Simple and convenient 2-key operation
- Very fast display: steady weight values within 3 s
- **1** Ideal as a compact letter and parcel scale, especially where space is limited
- **2** Ideal as a grading, commissioning or simple checkweighing scale in production or dispatch
- Protective working cover included with delivery


Technical data

- Large LCD display, digit height 25 mm
- Dimensions weighing surface, plastic, W×D 253×228 mm
- Overall dimensions W×D×H 270×323×110 mm
- Optional battery operation, 9 V block not included in scope of delivery, operating time up to 12 h, AUTO-OFF function to preserve the battery
- Net weight approx. 2,4 kg
- Permissible ambient temperature 5 °C/35 °C

Accessories

- Protective working cover, scope of delivery 5 items, KERN FCB-A02S05, **€ 52,-**
- **3** Stainless steel weighing plate, robust, removable, for easy cleaning, KERN FCE-A01, **€ 40,-**
- Internal rechargeable battery pack, operating time up to 20 h without backlight, charging time approx. 10 h, KERN FCB-A01, **€ 54,-**

STANDARD



OPTION



Model	Weighing capacity [Max] kg	Readability [d] g	Reproducibility g	Linearity g	Price excl. of VAT ex works €	Options	
						DAKKS Calibr. Certificate	
KERN						DAKKS KERN	€
FCE 3K1N	3	1	2	± 3	135,-	963-127	103,-
FCE 6K2N	6	2	2	± 4	135,-	963-128	124,-
FCE 15K5N	15	5	10	± 15	135,-	963-128	124,-
FCE 30K10N	30	10	10	± 30	135,-	963-128	124,-

NEW

The new FCB: Checkweighing and portioning scale with up to three interfaces, with optional verification

Features

- Standardised, convenient KERN concept of operation, consistency across products in terms of design, menu structure, button functions, interface connection and interface protocol
- Compact size
- KERN Universal Port (KUP): permits the connection of an external KUP interface adapter, such as, for example, RS-232, USB, Bluetooth, WiFi or Ethernet, for the exchange of data and control commands, without any installation outlay. Available as an option: RS-232, USB, Ethernet, WiFi, Bluetooth

- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers. For further information on KUP and KCP see page 18/19
- Thanks to battery operation/rechargeable battery operation (optional), compact, lightweight construction, it is suitable for the use in several locations
- Weighing with tolerance range: a visual and audible signal helps with portioning, dispensing or grading
- Summation of weight values
- Protective working cover included with delivery

Technical data

- Backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, W×D 252×225 mm
- Overall dimensions W×D×H 322×267×91 mm
- Net weight approx. 3,8 kg
- Permissible ambient temperature
KERN FCB: 0 °C/40 °C
KERN FCB-M: -10 °C/40 °C


Accessories

- Protective working cover, scope of delivery 5 items, KERN YBA-A14S05, **€ 52,-**
- Internal rechargeable battery pack, operating time up to 48 h without backlight, charging time approx. 8 h, KERN YKR-01, **€ 35,-**
- Signal lamp for visual support of weighing with tolerance range. connection is only possible in combination with KUP-01 (RS-232 interface), KERN CFS-A03, **€ 310,-**
- External data interface RS-232, interface cable included, KERN KUP-01, **€ 60,-**
- External data interface USB, interface cable included, KERN KUP-03, **€ 75,-**
- Ethernet interface adapter, KERN KUP-04, **€ 115,-**
- WiFi interface adapter, KERN KUP-05, **€ 75,-**
- Bluetooth interface adapter, KERN KUP-06, **€ 99,-**
- Extension box for connecting up to three interfaces in parallel, KERN KUP-13, **€ 75,-**
- Further details, plenty of further accessories and suitable printers see *Accessories*

STANDARD



OPTION



FACTORY



Model	Weighing capacity [Max]	Readability [d]	Verification value [e]	Minimal load [Min]	Smallest part weight (Normal) g/piece	Price excl. of VAT ex works €	Options			
							Verification	€	DAkkS	Certificate
KERN							KERN		DAkkS	
FCB 6K-5	6	0,05	-	-	0,5	330,-	-	-	963-128	124,-
FCB 8K0.1	8	0,1	-	-	1	275,-	-	-	963-128	124,-
FCB 12K-4	12	0,1	-	-	1	330,-	-	-	963-128	124,-
FCB 12K1	12	1	-	-	10	220,-	-	-	963-128	124,-
FCB 30K-4	30	0,2	-	-	2	330,-	-	-	963-128	124,-
FCB 30K1	30	1	-	-	10	260,-	-	-	963-128	124,-

Multi-division balance, with increasing or decreasing load, it switches automatically to the next largest or smallest weighing range [Max] and readout [d].

FCB 6K-3DM	NEW	3 6	1 2	1 2	20	2	300,-	965-228	84,-	963-128	124,-
FCB 15K-3DM	NEW	6 15	2 5	2 5	40	5	300,-	965-228	84,-	963-128	124,-
FCB 30K-3DM	NEW	15 30	5 10	5 10	100	10	300,-	965-228	84,-	963-128	124,-

Note: For devices that require verification (conformity assessment according to NAWI 2014/31/EU), please include the verification when placing your order.

The initial verification is not possible after delivery. Please inform the full address of the location of use for the initial verification.

NEW New model



Technical data

- Large backlit LCD display, digit height 25 mm
- Dimensions weighing surface, stainless steel, W×D 340×240 mm
- Overall dimensions W×D×H, 350×390×120 mm
- Optional battery operation, 4×1.5 V AA not included in scope of delivery, operating time up to 20 h
- Net weight approx. 7 kg
- Permissible ambient temperature -10 °C/40 °C

Accessories

- Protective working cover, scope of delivery 5 items, KERN FKB-A02S05, **€ 52,-**
- Internal rechargeable battery pack, operating time up to 48 h without backlight, charging time approx. 8 h, KERN YKR-01, **€ 35,-**
- Schnittstellenadapter USB, KERN KUP-03, **€ 75,-**
- Schnittstellenadapter RS-232, KERN KUP-01, **€ 60,-**
- Bluetooth interface adapter, KERN KUP-06, **€ 99,-**
- WiFi interface adapter, KERN KUP-05, **€ 75,-**
- Ethernet interface adapter, KERN KUP-04, **€ 115,-**
- Extension box for connecting up to three interfaces in parallel, KERN KUP-13, **€ 75,-**
- Tare pan made from stainless steel, ideal for weighing loose small parts as well as fruits, vegetables, etc., overall dimensions W×D×H 400×300×45 mm, KERN RFS-A02, **€ 75,-**
- Further details, plenty of further accessories and suitable printers see *Accessories*

High resolution bench scale with large weighing range and robust stainless steel weighing plate

Features


- Thanks to the high resolution of up to 360.000 points it is ideal for high-precision weighing in the industrial field
- Robust plastic die-cast housing: maintains the stability, protects the weighing technology elements and is robust enough to cope with everyday use
- KERN Universal Port (KUP): permits the connection of an external KUP interface adapter, such as, for example, RS-232, USB, Bluetooth, WiFi or Ethernet, for the exchange of data and control commands, without any installation outlay

- KERN Communication Protocol (KCP): The KCP permits searching and remote control of the balance using external control devices or computers
- PRE-TARE function for manual subtraction of a known container weight, useful for checking fill-levels
- Freely programmable weighing unit, e.g. display direct in special units such as length of wire g/m, surface weight g/m², or else
- Level indicator and levelling feet for precise levelling of the scale, fitted as standard
- Protective working cover included with delivery

STANDARD



OPTION



Model	Weighing capacity [Max] kg	Readability [d] g	Reproducibility g	Linearity g	Smallest part weight (Normal) g/piece	Resolution Points	Price excl. of VAT ex works €	Options	
								DAkkS KERN	Calibr. Certificate €
KERN									
FKB 6K0.02	6	0,02	0,04	± 0,1	0,2	300.000	530,-	963-128	124,-
FKB 8K0.05	8	0,05	0,05	± 0,15	0,5	160.000	510,-	963-128	124,-
FKB 16K0.05	16	0,05	0,1	± 0,25	0,5	320.000	550,-	963-128	124,-
FKB 8K0.1	8	0,1	0,1	± 0,3	1	80.000	360,-	963-128	124,-
FKB 16K0.1	16	0,1	0,1	± 0,3	1	160.000	510,-	963-128	124,-
FKB 15K0.5	15	0,5	0,5	± 1,5	10	30.000	385,-	963-128	124,-
FKB 36K0.1	36	0,1	0,2	± 0,5	1	360.000	560,-	963-128	124,-
FKB 36K0.2	36	0,2	0,4	± 1	2	180.000	560,-	963-128	124,-
FKB 65K0.2	65	0,2	0,4	± 1	2	325.000	540,-	963-129	153,-
FKB 30K1	30	1	1	± 3	20	30.000	340,-	963-128	124,-
FKB 65K1	65	1	1	± 3	20	65.000	360,-	963-129	153,-

The oldest Precision Balance Factory in Germany

KERN & SOHN GmbH

Balances, Test Weights, Microscopes,
DAkkS Calibration Laboratory

Ziegelei 1
72336 Balingen
Germany
Tel. +49 7433 9933-0
info@kern-sohn.com
www.kern-sohn.com

Discover the multifaceted World of Balances, Microscopes and Measuring Technology from KERN online: www.kern-sohn.com

- Full KERN & SAUTER Product Range
- Convenient 24/7 Ordering
- Selection of more than 5,000 Items across Weighing and Measuring Technology, Optical Instruments as well as Accessories and Services
- Extensive Information and useful Download Options
- Technical Product Data Sheets
- Operating Instructions
- Descriptive Image and Video Material
- Useful KERN Services
- Technical Glossary
- KERN Dealer Portal
- Practical Filter and Search Functions



Follow us on our social media
channels too



Printed in Germany by KERN & SOHN GmbH
z-cb-en-kp-20251

